

CORRECTED  
VERSION\*

CORRECTED  
VERSION\*\*

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04L 12/56, H04Q 11/04		A1	(11) International Publication Number: WO 98/29992
			(43) International Publication Date: 9 July 1998 (09.07.98)
(21) International Application Number: PCT/US97/24216		(81) Designated States: CA, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 29 December 1997 (29.12.97)			
(30) Priority Data: 08/775,157 31 December 1996 (31.12.96) US		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(71) Applicant (for all designated States except US): NORTHERN TELECOM LIMITED [CA/CA]; Patent Dept. NTPAT, P.O. Box 3511, Station "C", Ottawa, Ontario K1Y 4H7 (CA).			
(72) Inventors; and (75) Inventors/Applicants (for US only): ABU-AMARA, Hosame, Hassan [US/US]; 1208 Horizon Trail, Richardson, TX 75081 (US); KOTAMARTI, Venkat [CA/US]; 6518 Cove Creek Pl., Dallas, TX 75240 (US).			
(74) Agents: MUSGROVE, Jack, V. et al.; Felsman, Bradley, Gunter & Dillon, LLP, Arboretum Point, Suite 350, 9505 Arboretum Boulevard, Austin, TX 78759 (US).			

(54) Title: METHOD AND SYSTEM FOR BANDWIDTH ALLOCATION FOR MULTIMEDIA SERVICES UNDER AGGREGATE TRAFFIC CONDITIONS



(57) Abstract

A method and system are provided for calculating the most efficient bandwidth allocation of multimedia traffic under aggregate traffic conditions within a shared transmission medium, such as an ATM network, in a manner which maximizes long-term revenue. First, the total number of service groups within the network is specified by a network operator or a network designer. Each service group may contain multiple different types of communication traffic. Thereafter, for each service group, the number of users who utilize the services within that service group is determined. The average idle sojourn time and average burst sojourn time for each system state are then determined for each service group. Next, a specification of the peak rate, the probability that a user will access the service during a specified busy period, and an average session duration are determined. A specification of the price of each service per unit time is then provided by the network operator as well as the total available bandwidth in bits per second. Thereafter, these parameters are utilized to partition the bandwidth within the network among the various service groups so as to maximize long-run average system revenue.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon		Republic of Korea	PT	Portugal		
CN	China	KR	Republic of Korea	RO	Romania		
CU	Cuba	KZ	Kazakhstan	RU	Russian Federation		
CZ	Czech Republic	LC	Saint Lucia	SD	Sudan		
DE	Germany	LI	Liechtenstein	SE	Sweden		
DK	Denmark	LK	Sri Lanka	SG	Singapore		
EE	Estonia	LR	Liberia				

## METHOD AND SYSTEM FOR BANDWIDTH ALLOCATION FOR MULTIMEDIA SERVICES UNDER AGGREGATE TRAFFIC CONDITIONS

### CROSS-REFERENCE TO RELATED APPLICATION

This application is related to co-pending United States Patent Application Serial No. \_\_\_\_\_, (Attorney Docket No. 0267AD-RR1154) and United States Patent Application Serial No. \_\_\_\_\_, (Attorney Docket No. 0267AD-RR1156), both filed of even date herewith by the inventors herein named. The aforementioned co-pending applications are hereby incorporated herein by reference thereto.

### BACKGROUND OF THE INVENTION

#### 1. Technical Field:

The present invention relates to improvements in network design and in particular to improved methods and systems for bandwidth allocation for multimedia services under aggregate traffic conditions. Still more particularly, the present invention relates to a method and system for bandwidth allocation for multimedia services within a shared transmission medium in a manner which maximizes long-run average revenue.

#### 2. Description of the Related Art:

No where has the explosion of modern technology been more evident than in the field of communication. The number and type of communication services has been rapidly expanding, including so-called "multimedia" services such as video teleconferencing, video/movies on demand and the like.

The intermixing of these multimedia services with traditional data and voice communications within a shared transmission medium has presented various design problems. For example, consider a system which receives packetized telecommunication traffic from  $n$  multimedia services which are queued either in one central queue or in multiple distributed queues wherein one queue is associated with each service. Thus, if more than  $n$  subscribers to the services are utilizing the network at any given time, the received packets which are not processed by the system are queued. During heavy use periods, as the number of users increase, and these queues become quite large, certain packets may be discarded based upon a priority scheme and delay will increase and quality of service will suffer.

In the past, attempts at statistically modeling aggregate traffic which originates from homogenous services with similar traffic types and similar characteristics have been proposed. For example, the Poisson Process is widely utilized to model aggregate traffic from voice sources. Similarly, the discreet Auto Regressive Process has been utilized to model aggregate traffic from video-teleconferencing sources. A Markov Modulated Poisson Process is often utilized to model aggregate traffic from data sources. These techniques typically require complex mathematical expressions which are not explicit and which require time-consuming numerical methods to solve.

Those skilled in the art will appreciate that an accurate model of aggregate traffic within a network may be utilized to partition system capacity among multiple services. In the prior art, networks typically follow either the so-called "complete sharing" approach or the "complete partitioning" approach. In the complete sharing approach, each of the services within the system share system bandwidth on a first-come first-served basis. This approach is simple and utilizes system bandwidth efficiently; however, it may not maximize system revenue in a manner which is desired, in view of the extensive expense undertaken in the establishment of such networks. In the complete partitioning approach, each system has

its own bandwidth and no two services share the same bandwidth. This approach can be utilized to maximize system revenue, for example, by assigning more bandwidth to expensive services than is assigned to lower priced services. However, the complete partitioning approach is not very flexible in that new services which are added to the network require a re-  
5 calculation of the assigned bandwidth. Additionally, complete partitioning will sometimes waste system bandwidth because services can not share available bandwidth within an another partition within the system bandwidth.

10 It should thus be apparent to those skilled in the art that a method and system for efficient allocation of bandwidth for multimedia services under aggregate traffic conditions would result in a network in which the operators' return for operation of the network could be enhanced over the long term.

## SUMMARY OF THE INVENTION

It is therefore one object of the present invention to provide an improved network design.

It is another object of the present invention to provide improved methods and systems for bandwidth allocation for multimedia services under aggregate traffic conditions.

It is yet another object of the present invention to provide an improved method and system for bandwidth allocation for multimedia services within a shared transmission medium in a manner which maximizes long-run average revenue.

The foregoing objects are achieved as is now described. A method and system are provided for calculating the most efficient bandwidth allocation for multimedia traffic under aggregate traffic conditions within a shared transmission medium, such as an ATM network, in a manner which maximizes long term revenue. First, the total number of service groups within the network is specified by a network operator or a network designer. Each service group may contain multiple different types of communication traffic. Thereafter, for each service group, the number of users who utilize the services within that service group is determined. The average idle sojourn time and average burst sojourn time for each system state are then determined for each service group. Next, a specification of the peak rate, the probability that a user will access the service during a specified busy period, and an average session duration are determined. A specification of the price of each service per unit time is then provided by the network operator as well as the total available bandwidth in bits per second. Thereafter, these parameters are utilized to partition the bandwidth within the network among the various service groups so as to maximize long-run average system revenue.

**BRIEF DESCRIPTION OF THE DRAWINGS**

5 The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 Figure 1 is a schematic representation of a communication network which can incorporate multimedia traffic within a shared transmission medium;

Figure 2 is a high level block diagram of a system for calculating bandwidth allocation for multimedia traffic under aggregate traffic conditions within a shared transmission medium; and

15 Figure 3 is a high level logic flowchart of the method for calculating bandwidth allocation for multimedia traffic under aggregate traffic conditions within a shared transmission medium in a manner which maximizes long-run average system revenue.

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

With reference now to the figures and in particular with reference to **Figure 1**, there is depicted a schematic representation of a communication network which incorporates multimedia traffic within a shared transmission medium. As illustrated, communication network **10** may include multiple transmission sources and receivers coupled together utilizing various transmission medium. For example, one type of network which may advantageously utilize the method and system of the present invention, is an ATM network which is utilized in conjunction with satellite communication. Thus, satellite **12** may communicate with earth station **14** over transmission medium **16**. Similarly transmission tower **18** may communicate with transmission tower **22** over transmission medium **20**. Of course, those skilled in the art will appreciate that transmission medium **16** will comprise a high frequency wide bandwidth radio frequency transmission medium; however, the method and system of the present invention will find application in any system in which aggregate multimedia traffic will occupy a shared transmission medium, such as, for example, a fiber optic transmission medium.

Referring now to **Figure 2** there is depicted a high level block diagram of a system for calculating bandwidth allocation for multimedia traffic under aggregate traffic conditions within a shared transmission medium in accordance with the present invention. As illustrated, the system depicted in **Figure 2** utilizing, as its central element, processor **30**. Processor **30** may comprise an appropriately programmed computer such as a personal computer, workstation or other suitable computer possessing sufficient processor assets and processing capability to create the model which will be described herein.

Those skilled in the art will appreciate that in order to maximize long-run average system revenue within a network, the allocation of bandwidth



within the network must occur in a manner which accurately reflects the desired investment return on the system and the actual utilization parameters for each service within the network. It must then be necessary to accurately describe the various types of aggregate traffic which originate from heterogeneous sources, which may include widely diverse characteristics. It is therefore imperative that the parameters utilized within this assessment be accurate so that the calculation of bandwidth allocation within the network can result in an efficient utilization of the network.

As depicted, processor 30 utilizes six different inputs to generate the desired bandwidth partitioning for maximum long-run average system revenue. Input 32, as depicted within Figure 2, comprises the total number of different service groups within the network. This number is typically provided by the network operator and/or network designer and, of course, may include different types of telecommunication traffic within each service group. As will be set forth in greater detail herein, services are typically grouped together based upon revenue parameters such as the price per unit time for each service within a particular service group. The services provided within each service group may include voice, data, teleconferencing, video on demand and other similar communication types.

Next, as specified at input 34, the maximum number of users who may utilize the services within a service group is determined. This number may be generated by measurements, research literature or standards bodies such as the International Telecommunication Union-Telecommunication (ITU-T). Alternatively, one technique for determining the total service capacity for multimedia services under aggregate traffic conditions is set forth within one of the above-referenced patent applications.

Next, for each service group, the average idle sojourn time and average burst sojourn time are determined for each system state as specified at input 36. Again, these values may be obtained from measurements of

existing networks, research literature or standards bodies such as the ITU-T. Alternately, one excellent technique for determining the average idle sojourn time and average burst sojourn time may be found within one of the co-pending patent applications referenced above.

5           Next, input 38 comprises a specification of the peak rate for each service, a determination of the probability that a user will access a particular service group during a busy period and the average session duration for each such access. These values may also be obtained from measurement, research literature or standards bodies.

10           Input 40 comprises a specification of the price of service per unit time. This number is typically provided by the network operator and/or network designer and is calculated based upon various market and technological factors.

15           Finally, the total available system bandwidth in bits per second is specified by the network operator or designer and serves as input 42 to system 30.

20           Each of these inputs is then combined within processor 30, in a manner which will be explained in greater detail herein, to result in a single output 44 which comprises a partitioning of the bandwidth available within the network among the various service groups so as to maximize long-run average system revenue.

25           Finally, with reference to Figure 3, there is depicted a high level flowchart of the method of bandwidth allocation for multimedia services under aggregate traffic conditions in accordance with the present invention. As illustrated, the process begins at block 50 and thereafter passes to block 52. Block 52 depicts the determination of the peak rate, average session duration and probability of user utilization for each service. These values are

expressed as a peak bandwidth requirement  $R_i$  for each service  $i$ , an average session duration  $S_i$  for each service  $i$  and a probability  $E_i$  that a user will utilize service  $i$  and these values may be obtained from network measurements, research literature or standards bodies such as the ITU-T.

Next, as depicted in block 54, the services are partitioned into service groups and the expected revenue from each service group is calculated. Thus, if  $K$  is the number of service groups, the value of  $K$  and the number and type of services within each service group can be selected based upon network operator system objectives. For example, services may be partitioned into three service groups, namely: Premium, a service group which contains those services having high service price per unit time; Extended, a service group which contains services having moderate service price per unit time; and, Basic, a service group which contains those services having inexpensive cost per unit time. Thus, in the present example, the number of service groups  $K$  will be three.

Thereafter, for each service  $i$ , let  $\text{price}(i)$  be the price of service  $i$  per unit time. For each service group  $k$ , let  $n_k$  be the number of users who utilize the service in service group  $k$ . Thereafter, the expected revenue  $r_k(n_k)$  for service group  $k$  may be defined as follows:

$$r_k(n_k) = \sum_{i \in k} \lambda_i \cdot E_i \cdot S_i \cdot \text{price}(i)$$

Next, the process passes to block 56. Block 56 illustrates the modeling of the aggregate traffic from the various traffic sources as a stochastic system. One excellent technique for modeling the aggregate traffic from heterogenous sources is set forth in the first copending patent application referenced above. Thereafter, a system state is defined for a service group as a tuple  $(n_1, n_2, \dots, n_k)$  which specifies that there are  $n_1$  calls in progress,  $n_2$  calls in progress,  $\dots$   $n_k$  calls in progress within the service group. For each service group  $k$ , the average idle sojourn time  $(1/\lambda_k(m))$  an

average burst sojourn time  $(1/\mu_k(m))$  for each system state can be determined, where  $m$  is the number of users of services in service group  $k$ . Thereafter, an activity ratio  $\rho_k(m)$  is defined as follows:  $\rho_k(m) = \lambda_k(m)/\mu_k(m)$

While described herein as a serial process, those skilled in the art will appreciate that the partitioning of services into service groups and the modeling of the aggregate traffic can be accomplished contemporaneously, rather than serially as depicted herein.

Next, the process passes to block 58. Block 58 illustrates the determination of the bandwidth to be assigned to each service group. Thus, for each service group  $k$ , let  $\beta_k$  be the bandwidth we wish to compute for service group  $k$ . Thereafter, let the peak bandwidth requirement  $G_k$  for each service group  $k$  be the maximum bandwidth requirement  $R_i$  for services  $i$  within service group  $k$ . Thereafter, we can define the long-run average revenue rate  $W_k(B_k)$  associated with service group  $k$  as follows:

$$W_k(\beta_k) = \frac{\sum_{n=0}^{\lfloor \beta_k / G_k \rfloor} \pi_k(n) \sigma_k(n)}{\sum_{n=0}^{\lfloor \beta_k / G_k \rfloor} \sigma_k(n)}, \text{ where } \sigma_k(n) = \prod_{m=0}^{n-1} \rho_k(m)$$

Next, if  $C$  is the peak network bandwidth, in order to find the value of  $B_k$  for each service group  $k$ , dynamic programming may be utilized to solve the following allocation problem:

$$\begin{array}{ll} \text{maximize} & \sum_{k=1}^K W_k(\beta_k) \\ \text{subject to} & \sum_{k=1}^K \beta_k = C, 0 \leq \beta_k \leq C, \beta_k \text{ is an integer, and } k = 1, \dots, K \end{array}$$

Finally, referring to block 60, the bandwidths for each service group are assigned based upon the calculations above. Thus, services which belong to the same service group will share a particular bandwidth allocation on a first-come first-served basis. Services which belong to different service groups will not share bandwidth. Therefore, the present system provides a variation of the complete sharing approach and complete partitioning approach wherein services are partitioned into service groups and each service within a particular service group enjoys a complete sharing approach for the bandwidth allocated to that service group. The process then passes to block 62 and terminates.

Upon reference to the foregoing, those skilled in the art will appreciate that by utilizing the modeling techniques set forth herein, the bandwidth allocation for multimedia services under aggregate traffic conditions may be calculated in a manner which maximizes long-run average revenue by combining a complete sharing bandwidth allocation approach with a complete partitioning bandwidth allocation approach in a manner which accurately and efficiently reflects the characteristics of the types of service within the network. The method and system of the present invention utilizes characterization of these services to accurately and efficiently allocate bandwidth within the network in a manner which will maximize long-run average system revenue.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

**CLAIMS:**

What is claimed:

- 1        1.     A method for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services under aggregate traffic conditions  
3        within a network having a shared transmission medium, said method for  
4        comprising the steps of:  
  
5                partitioning said plurality of heterogenous telecommunication services  
6                into a plurality of service groups;  
  
7                assigning a selected portion of bandwidth within said shared  
8                transmission medium to an associated one of said plurality of  
9                service groups; and  
  
10               allocating bandwidth within said assigned selected portion to  
11               telecommunication services within an associated service group  
12               on a first-come, first-served basis.
- 1        2.     The method for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 1 wherein said  
3        step of partitioning said plurality of heterogenous telecommunication groups  
4        into a plurality of service groups further comprises the step of assigning each  
5        telecommunication service to a particular service group based upon a price  
6        per unit time for each telecommunication service.
- 1        3.     The method for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 2 further  
3        including the step of creating a multi-state model of said plurality of  
4        heterogenous telecommunication services under aggregate traffic conditions.

1        4.    The method for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 3. further  
3        including the step of utilizing said model of said plurality of heterogenous  
4        telecommunication services under aggregate traffic conditions to determine  
5        an average idle sojourn time and average burst sojourn time for each state  
6        within said model.

1        5.    The method for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 3 wherein said  
3        step of assigning a selected portion of bandwidth within said shared  
4        transmission medium to an associated one of said plurality of service groups  
5        comprises the step of assigning a selected portion of bandwidth within said  
6        shared transmission medium based upon said price per unit time for each  
7        telecommunication service within a selected service group in order to  
8        maximize long-run average network revenue.

1        6.    A system for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services under aggregate traffic conditions  
3        within a network having a shared transmission medium, said system  
4        comprising:

5                means for partitioning said plurality of heterogenous  
6                telecommunication services into a plurality of service groups;

7                means for assigning a selected portion of bandwidth within said  
8                shared transmission medium to an associated one of said  
9                plurality of service groups; and

10               means for allocating bandwidth within said assigned selected portion  
11               to telecommunication services within an associated service  
12               group on a first-come, first-served basis.

1        7.    The system for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 6 wherein said  
3        means for partitioning said plurality of heterogenous telecommunication  
4        groups into a plurality of service groups further comprises means for  
5        assigning each telecommunication service to a particular service group based  
6        upon a price per unit time for each telecommunication service.

1        8.    The system for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 7 further  
3        including means for creating a multi-state model of said plurality of  
4        heterogenous telecommunication services under aggregate traffic conditions.

1        9.    The system for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 8 further  
3        including means for utilizing said model of said plurality of heterogenous  
4        telecommunication services under aggregate traffic conditions to determine  
5        an average idle sojourn time and average burst sojourn time for each state  
6        within said model.

1        10.   The system for efficient bandwidth allocation for a plurality of  
2        heterogenous telecommunication services according to Claim 9 wherein said  
3        means for assigning a selected portion of bandwidth within said shared  
4        transmission medium to an associated one of said plurality of service groups  
5        comprises means for assigning a selected portion of bandwidth within said  
6        shared transmission medium based upon said price per unit time for each  
7        telecommunication service within a selected service group in order to  
8        maximize long-run average network revenue.



1/3




Fig. 1




Fig. 2

3/3




Fig. 3

# INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/US 97/24216

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04L12/56 H04011/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04L H040

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X	US 5 274 644 A (BERGER ARTHUR W ET AL) 28 December 1993 see column 3, line 9-61 ---	1.6
X	JI H ET AL: "STATISTICAL RESOURCE ALLOCATION AND PRICING IN BROADBAND COMMUNICATION NETWORKS" BROADBAND COMMUNICATIONS. GLOBAL INFRASTRUCTURE FOR THE INFORMATION AGE. PROCEEDINGS OF THE INTERNATIONAL IFIP-IEEE CONFERENCE ON BROADBAND COMMUNICATIONS, CANADA, 1996. April 1996. MASON L (ED ). pages 247-258. XP000702584 see page 249, line 5-6 see paragraph 2 see page 251, line 18-22 ---	1.6
A	---	2.7
	-/--	

☒ Further documents are listed in the continuation of box C

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "S" document member of the same patent family

Date of the actual completion of the international search

15 May 1998

Date of mailing of the international search report

25/05/1998

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040. Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Dhondt, E

# INTERNATIONAL SEARCH REPORT

Int l tional Application No  
PCT/US 97/24216

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X	HONGBIN JI ET AL: "GOS-BASED PRICING AND RESOURCE ALLOCATION FOR MULTIMEDIA BROADBAND NETWORKS" PROCEEDINGS OF IEEE INFOCOM 1996. CONFERENCE ON COMPUTER COMMUNICATIONS. FIFTEENTH ANNUAL JOINT CONFERENCE OF THE IEEE COMPUTER AND COMMUNICATIONS SOCIETIES. NETWORKING THE NEXT GENERATION SAN FRANCISCO. MAR. 24 - 28. 1996. vol. VOL. 3, no. CONF. 15. 24 March 1996. INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS. pages 1020-1027. XP000622234	1.6
A	see page 1020. left-hand column. line 36 - right-hand column. line 10 see paragraph 2.2 see page 1023. right-hand column. line 21-24	2.7
A	----- KELLY F P: "TARIFFS AND EFFECTIVE BANDWIDTHS IN MULTISERVICE NETWORKS" FUNDAMENTAL ROLE OF TELETRAFFIC IN THE EVOLUTION OF TELECOMMUNICATI NETWORKS. PROCEEDINGS OF THE 14TH. INTERNATIONAL TELETRAFFIC CONGRESS - ITC 1 JUAN-LES-PINS. JUNE 6 - 10. 1994. no. VOL. 1A. 6 June 1994. LABETOULLE J:ROBERTS J W (EDS ). pages 401-410. XP000593430 see page 404. line 16-28	2.7
A	----- LOW S H ET AL: "A NEW APPROACH TO SERVICE PROVISIONING IN ATM NETWORKS" IEEE / ACM TRANSACTIONS ON NETWORKING. vol. 1. no. 5. 1 October 1993. pages 547-553. XP000420853 see page 548. right-hand column. line 30-32 -----	2.7

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/24216

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5274644 A	28-12-93	NONE	